

# Product data sheet

Specifications



## TeSys Deca, thermal overload relay, 63 to 80 A, class 10A, for LC1D80 and LC1D95

LRD3363

**Product availability: Stock - Normally stocked in distribution facility**

### Main

Range	TeSys
product name	TeSys LRD TeSys Deca
Product or Component Type	Differential thermal overload relay
Device short name	LRD
Relay application	Motor protection
Product Compatibility	LC1D80 LC1D95
Network type	CC CA
Thermal overload class	Class 10A IEC 60947-4-1
Thermal protection adjustment range	63...80 A
[Ui] rated insulation voltage	Power circuit 1000 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL

### Complementary

Network Frequency	0...400 Hz
Mounting support	Plate, with specific accessories Rail, with specific accessories Under contactor
Tripping threshold	1.14 +/- 0.06 I <sub>r</sub> IEC 60947-4-1
Auxiliary contact composition	1 NO + 1 NC
[I <sub>th</sub> ] conventional free air thermal current	5 A signalling circuit
Permissible current	0.72 A 500 V AC-15 signalling circuit 0.06 A 440 V DC-13 signalling circuit
[U <sub>e</sub> ] rated operational voltage	1000 V AC 0...400 Hz power circuit IEC 60947-4-1
Associated fuse rating	4 A gG for signalling circuit 4 A BS for signalling circuit
[U <sub>imp</sub> ] rated impulse withstand voltage	6 kV IEC 60947-1
Phase failure sensitivity	Tripping current 130 % of I <sub>r</sub> on two phase, the last one at 0
Control type	Red push-button stop Blue push-button reset
Temperature compensation	-4...140 °F (-20...60 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Connections - terminals</b>	Power circuit screw clamp terminals 1 0.006...0.05 in <sup>2</sup> (4...35 mm <sup>2</sup> ) flexible without cable end Power circuit screw clamp terminals 1 0.006...0.05 in <sup>2</sup> (4...35 mm <sup>2</sup> ) flexible with cable end Power circuit screw clamp terminals 1 0.006...0.05 in <sup>2</sup> (4...35 mm <sup>2</sup> ) solid without cable end Control circuit screw clamp terminals 2 0.002...0.004 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) flexible without cable end Control circuit screw clamp terminals 2 0.002...0.004 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) flexible with cable end Control circuit screw clamp terminals 2 0.002...0.004 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) solid without cable end
<b>Tightening torque</b>	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Power circuit 79.7 lbf.in (9 N.m) screw clamp terminals
<b>Height</b>	3.2 in (81 mm)
<b>Width</b>	2.8 in (70 mm)
<b>Depth</b>	4.5 in (115 mm)
<b>Net Weight</b>	1.12 lb(US) (0.51 kg)

## Environment

<b>Climatic withstand</b>	IACS E10
<b>IP degree of protection</b>	IP20 conforming to IEC 60529
<b>Ambient air temperature for operation</b>	-4...140 °F (-20...60 °C) without derating IEC 60947-4-1
<b>Ambient Air Temperature for Storage</b>	-76...158 °F (-60...70 °C)
<b>Flame retardance</b>	V1 conforming to UL 94
<b>Mechanical robustness</b>	Vibrations 6 Gn IEC 60068-2-6 Shocks 15 Gn for 11 ms IEC 60068-2-7
<b>Dielectric strength</b>	2.2 kV 50 Hz IEC 60947-1
<b>Standards</b>	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495
<b>Product Certifications</b>	IEC UL CSA CCC EAC ATEX INERIS UKCA

## Ordering and shipping details

<b>Category</b>	US10I1222347
<b>Discount Schedule</b>	0I12
<b>GTIN</b>	3389110520002
<b>Returnability</b>	Yes
<b>Country of origin</b>	FR

## Packing Units

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	3.15 in (8.000 cm)
<b>Package 1 Width</b>	3.54 in (9.000 cm)
<b>Package 1 Length</b>	4.72 in (12.000 cm)
<b>Package 1 Weight</b>	18.060 oz (512.000 g)
<b>Unit Type of Package 2</b>	S02
<b>Number of Units in Package 2</b>	12
<b>Package 2 Height</b>	5.91 in (15.000 cm)
<b>Package 2 Width</b>	11.81 in (30.000 cm)
<b>Package 2 Length</b>	15.75 in (40.000 cm)
<b>Package 2 Weight</b>	14.264 lb(US) (6.470 kg)
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	192
<b>Package 3 Height</b>	29.53 in (75.000 cm)
<b>Package 3 Width</b>	23.62 in (60.000 cm)
<b>Package 3 Length</b>	31.50 in (80.000 cm)
<b>Package 3 Weight</b>	252.359 lb(US) (114.468 kg)

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 6

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No