

Reference: 6SL3210-5BE25-5UV0

SINAMICS V20 3AC380-480V -15/+10%
47-63HZ RATED POWER 5.5KW WITH
150% OVERLOAD FOR 60SEC
UNFILTERED I/O-INTERFACE: 4DI,
2DO,2AI,1AO FIELDBUS: USS/ MODBUS
RTU WITH INBUILT BOP PROTECTION:
IP20/ UL OPEN TYPE SIZE:FSC
184X182X169(WXHxD)

Buy it at [Electric Automation Network](#)



Product	
Article Number (Market Facing Number)	6SL3210-5BE25-5UV0
Product Description	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 5.5KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSC 184X182X169(WXHxD)
Product family	SINAMICS V20 basic converters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group / Headquarter Price Group	325 / 350
List Price	Show prices
Customer Price	Show prices
Metal Factor	None
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99H
Standard lead time ex-works	3 Day/Days
Net Weight (kg)	2,400 Kg
Product Dimensions (W x L x H)	Not available
Packaging Dimension	240,00 x 240,00 x 220,00
Package size unit of measure	MM
Quantity Unit	1 Piece

Packaging Quantity	1																																							
Atd>																																								
EAN	6940408102774																																							
UPC	887621056254																																							
Commodity Code	85044084																																							
LKZ_FDB/ CatalogID	SINAMICS V20																																							
Product Group	5681																																							
Country of origin	China																																							
Compliance with the substance restrictions according to RoHS directive	Since: 05/07/10																																							
Product class	C: products manufactured / produced to order, which cannot be reused or re-utilised or be returned against credit.																																							
Obligation Category for taking back electrical and electronic equipment after use	No obligation to take back electrical and electronic equipment after use																																							
Classifications																																								
	<table border="1"> <thead> <tr> <th></th> <th>Version</th> <th>Classification</th> </tr> </thead> <tbody> <tr> <td>eClass</td> <td>5.1</td> <td>27-02-31-01</td> </tr> <tr> <td>eClass</td> <td>6</td> <td>27-02-31-01</td> </tr> <tr> <td>eClass</td> <td>7.1</td> <td>27-02-31-01</td> </tr> <tr> <td>eClass</td> <td>8</td> <td>27-02-31-01</td> </tr> <tr> <td>eClass</td> <td>9</td> <td>27-02-31-01</td> </tr> <tr> <td>eClass</td> <td>9.1</td> <td>27-02-31-01</td> </tr> <tr> <td>ETIM</td> <td>4</td> <td>EC001857</td> </tr> <tr> <td>ETIM</td> <td>5</td> <td>EC001857</td> </tr> <tr> <td>ETIM</td> <td>6</td> <td>EC001857</td> </tr> <tr> <td>IDEA</td> <td>4</td> <td>5104</td> </tr> <tr> <td>UNSPSC</td> <td>14</td> <td>39-12-10-07</td> </tr> <tr> <td>UNSPSC</td> <td>15</td> <td>39-12-10-07</td> </tr> </tbody> </table>		Version	Classification	eClass	5.1	27-02-31-01	eClass	6	27-02-31-01	eClass	7.1	27-02-31-01	eClass	8	27-02-31-01	eClass	9	27-02-31-01	eClass	9.1	27-02-31-01	ETIM	4	EC001857	ETIM	5	EC001857	ETIM	6	EC001857	IDEA	4	5104	UNSPSC	14	39-12-10-07	UNSPSC	15	39-12-10-07
	Version	Classification																																						
eClass	5.1	27-02-31-01																																						
eClass	6	27-02-31-01																																						
eClass	7.1	27-02-31-01																																						
eClass	8	27-02-31-01																																						
eClass	9	27-02-31-01																																						
eClass	9.1	27-02-31-01																																						
ETIM	4	EC001857																																						
ETIM	5	EC001857																																						
ETIM	6	EC001857																																						
IDEA	4	5104																																						
UNSPSC	14	39-12-10-07																																						
UNSPSC	15	39-12-10-07																																						