

Reference: 3SU1062-2DL40-0AA0

SELECTOR SWITCH, CAN BE ILLUM.,  
30MM, ROUND, METAL, MATT, GREEN,  
SHORT SELECTOR SWITCH, FRONT RING  
FOR FLAT INSTALL., 3 SWITCH POSITIONS  
I-O-II, LATCHING, ACTUATING ANGLE  
2X45 DEG., 10:30H/12H/13:30H

Buy it at Electric Automation Network



product brand name	SIRIUS ACT
Product designation	Control and signaling units
Design of the product	Selector switch
Enclosure:	
Number of command points	1
Actuator:	
Design of the operating mechanism	Selector switch, short black handle and front ring for flush installation
Manner of function of the actuating element	maintained, 2x45° (10:30h/12h/13:30h)
Product extension optional Light source	Yes
Color of the actuating element	Green
Material of the actuating element	plastic
Shape of the actuating element	Handle
Outer diameter of the actuating element	38 mm
Number of switching positions	3
Actuating angle	
clockwise	45°
anticlockwise	45°
Front ring:	
Product component front ring	Yes
Design of the front ring	Flat

Material of the front ring	Metal, matt
Color of the front ring	sand gray
General technical data:	
Protection class IP	IP66, IP67, IP69(IP69K)
Degree of protection NEMA rating	NEMA 1, 2, 3, 3R, 4, 4X, 12
Shock resistance	
acc. to IEC 60068-2-27	Sinusoidal half-wave 50 g / 11 ms
for railway applications acc. to DIN EN 61373	Category 1, Class B
Vibration resistance	
acc. to IEC 60068-2-6	10 ... 500 Hz: 5g
for railway applications acc. to DIN EN 61373	Category 1, Class B
Operating frequency maximum	1 800 1/h
Mechanical service life (switching cycles)	
typical	300 000
Equipment marking	
acc. to DIN EN 61346-2	S
acc. to DIN EN 81346-2	S
Safety related data:	
B10 value	
with high demand rate acc. to SN 31920	300 000
Proportion of dangerous failures	
with low demand rate acc. to SN 31920	20 %
with high demand rate acc. to SN 31920	20 %
Failure rate [FIT]	
with low demand rate acc. to SN 31920	100 FIT
T1 value for proof test interval or service life acc. to IEC 61508	20 y
Ambient conditions:	
Ambient temperature	
during operation	-25 ... +70 °C
during storage	-40 ... +80 °C
Environmental category during operation acc. to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95 %)
Installation/ mounting/ dimensions:	
Height	44.8 mm
Witd>	38 mm
Shape of the installation opening	round
Mounting diameter	30.5 mm
Positive tolerance of installation diameter	0.5 mm

Mounting height	22.1 mm
Installation width	38 mm
Installation depth	32.1 mm