



- Smooth and slimline profile
- Clip on front plate for clean screwless aesthetic
- Silver Finish
- 100W SBL LED Load

Product Specification Data

Revision Date: 11/10/2024

Product Standard/s	BS EN 60669-1
Terminal Capacity L&N	4 x 1.0, 3 x 1.5, 1 x 2.5 mm ²
Frequency	50 Hz
Printing	Bell Symbol
CE Conformity	Yes
UKCA Conformity	Yes
Wiring system	Two-way switch
Method of operation	Rocker/button
Assembly arrangement	Basic element
Number of modules (module system)	0
Push button switch	Yes
Number of rockers	1
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	No
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	Silver
Illumination	No
Function lighting	Other
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	10 A
Connection type	Screwed terminal
Min. depth of built-in installation box	16 mm



Venus Electric
Address: Salah Al-Din Al Ayoubi St, Jabal Alhussein,
Amman
Phone: +962 79196 6817
Fax: 064640203
Email: info@venuselect.com
Website: www.venuselect.com