




Main/Emergency-Off Switches

- Enclosed switches with insulated enclosure (polycarbonate)
- 2 up to 8 pole
- 20 A up to 125 A
- IP66



Switching programme	Rated data (IEC 60947)			Enclosure dimension (H × W × D) (mm)	Padlock device N-handle yellow/red  IP66
	Operat. current I _e	Operational power (at 380–440 V)			Order code number
	AC-21A (A)	AC-23A (kW)	AC-3 (kW)		
41200 – 2 pole – without auxiliary contacts 	20	5.5	3.7	125 × 100 × 85	H216-41200-700N4 ¹
	25	7.5	5.5	125 × 100 × 85	H220-41200-700N4 ¹
	32	11	7.5	125 × 100 × 85	H226-41200-700N4 ¹
41300 – 3 pole – without auxiliary contacts 	20	5.5	3.7	100 × 80 × 65	H212-41300-077N4 ²
	63	22	18.5	250 × 160 × 95	H406-41300-177N4 ²
	63	22	18.5	320 × 220 × 180	H406-41300-471N4 ¹
	80	30	22	250 × 160 × 95	H408-41300-177N4 ²
	80	30	22	320 × 220 × 180	H408-41300-471N4 ¹
	100	37	30	250 × 160 × 95	H410-41300-177N4 ²
	100	37	30	320 × 220 × 180	H410-41300-471N4 ¹
	125	45	37	320 × 220 × 180	H412-41300-471N4 ¹
	41400 – 4 pole – without auxiliary contacts – neutral contact early make/late break 	20	5.5	3.7	100 × 80 × 65
63		22	18.5	250 × 160 × 95	H406-41400-177N4 ²
63		22	18.5	320 × 220 × 180	H406-41400-471N4 ¹
63		22	18.5	320 × 220 × 180	H406-41400-461N4 ¹ (w/o N-terminal)
80		30	22	250 × 160 × 95	H408-41400-177N4 ²
80		30	22	320 × 220 × 180	H408-41400-471N4 ¹
80		30	22	320 × 220 × 180	H408-41400-461N4 ¹ (w/o N-terminal)
100		37	30	250 × 160 × 95	H410-41400-177N4 ²
100		37	30	320 × 220 × 180	H410-41400-471N4 ¹
100		37	30	320 × 220 × 180	H410-41400-461N4 ¹ (w/o N-terminal)
125		45	37	320 × 220 × 180	H412-41400-471N4 ¹
125		45	37	320 × 220 × 180	H412-41400-461N4 ¹ (w/o N-terminal)



¹ Cover interlock in ON position

² Cover security through screw shroud

Further switching programmes please see Main Catalogue.

Disconnect Switches

Main/Emergency-Off Switches **Enclosed Switches** – Insulated Enclosure

Switching programme	Rated data (IEC 60947)			Enclosure dimension (H × W × D) (mm)	Padlock device N-handle yellow/red   IP66
	Operat. current I _e	Operational power (at 380–440 V)			Order code number
41600 – 6 pole – without auxiliary contacts 	20	5.5	3.7	250 × 160 × 95	H216-41600-477N4 ¹
	25	7.5	5.5	250 × 160 × 95	H220-41600-477N4 ¹
	32	11	7.5	250 × 160 × 95	H226-41600-477N4 ¹
	40	15	11	250 × 160 × 95	H233-41600-477N4 ¹
41800 – 8 pole – without auxiliary contacts – 2 neutral contacts early make/late break 	20	5.5	3.7	250 × 160 × 95	H216-41800-477N4 ¹
	20	5.5	3.7	250 × 160 × 95	H216-41800-467N4 ¹ (w/o N-terminal)
	25	7.5	5.5	250 × 160 × 95	H220-41800-477N4 ¹
	25	7.5	5.5	250 × 160 × 95	H220-41800-467N4 ¹ (w/o N-terminal)
	32	11	7.5	250 × 160 × 95	H226-41800-477N4 ¹
	32	11	7.5	250 × 160 × 95	H226-41800-467N4 ¹ (w/o N-terminal)
	40	15	11	250 × 160 × 95	H233-41800-477N4 ¹
	40	15	11	250 × 160 × 95	H233-41800-467N4 ¹ (w/o N-terminal)




¹ Without cover interlock




Further switching programmes please see Main Catalogue.

Dimensions in mm:

Setup of order code number

Type	Switching progr.	Mtg. form
H406	41400	177N4
Order code no.	H406-41400-177N4	





Insulated enclosures **100 × 80 × 65 mm / 125 × 100 × 85 mm / 250 × 160 × 95 mm:**

Types H212 / H216 / H220 / H226 / H406 / H408 / H410 / H412:

Mounting form	H1	B1	T1	T2	2×M	H2
077N4	100	80	65	33	20	90
700N4	125	100	85	33	20/25	115
177N4	250	160	95	45	25/32	240
467N4	250	160	95	33	25/32	240
477N4	250	160	95	33	25/32	240

Insulated enclosure **320 × 220 × 180 mm:**

Types H216 / H220 / H226 / H233 / H406 / H408 / H410 / H412:

Mounting form	H1	B1	T1	T2	H2	B2
461N4	320	220	180	45	293	193
471N4	320	220	180	45	293	193