

General Information

Extended Product Type:	CA5X-10
Product ID:	1SBN019010R1010
EAN:	3471522387905
Catalog Description:	CA5X-10 Auxiliary contact block
Long Description:	CA5X-10 Auxiliary Contact Block

Additional Information

ABB Industrial IT Suite:	Control IT
CB Certificate:	CB_CN28662
CCC Certificate:	CCC_2013010304656838
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-5-1, q = 40 °C 16 A
Country of Origin:	India (IN)
Customs Tariff Number:	85030099
Data Sheet, Technical Information:	1SXF101004C2001
Declaration of Conformity - CE:	1SBD250013U1000
EAN:	3471522387905
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SBB910513D4501
Invoice Description:	CA5X-10 Auxiliary contact block
Maximum Electrical Switching Frequency:	AC-15 1200 cycles per hour DC-13 900 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Minimum Order Quantity:	10 piece
Number of Auxiliary Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Object Classification Code:	K
Package Level 1 EAN:	3471522387905
Package Level 1 Gross Weight:	0.14 kg
Package Level 1 Height:	40 mm
Package Level 1 Length:	130 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	65 mm
Package Level 2 Height:	300 mm
Package Level 2 Length:	380 mm
Package Level 2 Units:	600 piece
Package Level 2 Width:	220 mm
Packing Type:	Box
Product Main Type:	Accessories for Block Contactors
Product Name:	Auxiliary Contact Block
Product Net Depth:	47 mm
Product Net Height:	36 mm
Product Net Weight:	0.013 kg
Product Net Width:	10 mm

PRODUCT REFERENCE:

10 11111

Product Packing Type:

Box

Rated Insulation Voltage (U_i):

acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V

Rated Operational Current AC-15 (I_a):

(220 / 240 V) 4 A
(24 / 127 V) 6 A
(690 V) 2 A
(380 / 440 V) 3 A

Rated Operational Current DC-13 (I_a):

(110 V) 0.55 A / 60 W
(125 V) 0.55 A / 69 W
(220 V) 0.30 A / 66 W
(24 V) 6 A / 144 W
(250 V) 0.30 A / 75 W
(400 V) 2.8 A / 134 W
(500 V) 1 A / 72 W

Rated Operational Voltage:

Auxiliary Circuit 690 V
Main Circuit 690 V

Rated Short-time Withstand Current (I_{cw}):

for 0.1 s 140 A
for 1 s 100 A

Selling Unit of Measure:

piece

Short Description:

CA5X-10 Auxiliary contact block

Suitable For:

AX06
AX09
AX12
AX18
AX25
AX32
AX40
AX50
AX65
AX80
AX95
AX115
AX150
NX

Terminal Type:

Screw Terminals

UNSPSC:

39121500



